

APPENDIX B
BUILDING CODE SUMMARY
FOR ALL COMMERCIAL PROJECTS
(EXCEPT 1 AND 2-FAMILY DWELLINGS AND TOWNHOUSES)
 (Reproduce the following data on the building plans sheet 1 or 2)

Name of Project: _____
 Address: _____
 Proposed Use: _____
 Owner or Authorized Agent: _____ Phone # _____
 Owned By: City/County Private State
 Code Enforcement Jurisdiction: City _____ County _____

LEAD DESIGN PROFESSIONAL: _____

DESIGNER	FIRM	NAME	LICENSE #	TELEPHONE #
Architectural	_____	_____	_____	(____)_____
Civil	_____	_____	_____	(____)_____
Electrical	_____	_____	_____	(____)_____
Fire Alarm	_____	_____	_____	(____)_____
Plumbing	_____	_____	_____	(____)_____
Mechanical	_____	_____	_____	(____)_____
Sprinkler-Standpipe	_____	_____	_____	(____)_____
Structural	_____	_____	_____	(____)_____
Retaining Walls >5' High	_____	_____	_____	(____)_____
Other	_____	_____	_____	(____)_____

YEAR EDITION OF CODE: _____
 New Construction Renovation (Existing Bldg) Upfit Alteration

BUILDING DATA

Construction Type: I-A I-B II-A II-B III-A III-B
 IV V-A V-B
 Mixed construction: No Yes Types _____
Sprinklers: No Yes NFPA 13 NFPA 13R NFPA 13D
Standpipes: No Yes Class I II III Wet Dry
Fire District: No Yes
Building Height: _____ Feet _____ Number of Stories Unlimited per _____
Mezzanine: No Yes
High Rise: No Yes Central Reference Sheet # (if provided) _____
Gross Building Area:

FLOOR	EXISTING (SQ FT)	NEW (SQ FT)	SUB-TOTAL
6 th Floor	_____	_____	_____
5 th Floor	_____	_____	_____
4 th Floor	_____	_____	_____
3 rd Floor	_____	_____	_____
2 nd Floor	_____	_____	_____
Mezzanine	_____	_____	_____
1 st Floor	_____	_____	_____
Basement	_____	_____	_____

TOTAL

ALLOWABLE AREA

- Primary Occupancy:** Assembly A-1 A-2 A-3 A-4 A-5
 Business Educational Factory-Industrial F-1 F-2
 High-Hazard H-1 H-2 H-3 H-4 H-5
 Institutional I-1 I-2 I-3 I-4
 I-3 Use Condition 1 2 3 4 5
 Mercantile Residential R-1 R-2 R-3 R-4
 Storage S-1 S-2 High-piled
 Utility and Miscellaneous Parking Garage Open Enclosed Repair

Secondary Occupancy: _____

- Special Occupancy:** 508.2 508.3 508.4 508.5 508.6 508.7 508.8

- Mixed Occupancy:** No Yes Separation: _____ Hr. Exception: _____

- Non-Separated Mixed Occupancy (302.3.2)

The required type of construction for the building shall be determined by applying the height and area limitations for each of the applicable occupancies to the entire building. The most restrictive type of construction, so determined, shall apply to the entire building.

- Separated Mixed Occupancy (302.3.3) - See below for area calculations

For each story, the area of the occupancy shall be such that the sum of the ratios of the actual floor area of each use divided by the allowable floor area for each use shall not exceed 1.

$$\frac{\text{Actual Area of Occupancy A}}{\text{Allowable Area of Occupancy A}} + \frac{\text{Actual Area of Occupancy B}}{\text{Allowable Area of Occupancy B}} \leq 1$$

$$\text{_____} + \text{_____} + \dots = \text{_____} \leq 1.00$$

STORY NO.	DESCRIPTION AND USE	(A) BLDG AREA PER STORY (ACTUAL)	(B) TABLE 503 ⁵ AREA	(C) AREA FOR OPEN SPACE INCREASE ¹	(D) AREA FOR SPRINKLER INCREASE ²	(E) ALLOWABLE AREA OR UNLIMITED ³	(F) MAXIMUM BUILDING AREA ⁴

¹ Open space area increases from Section 506.2 are computed thus:

- Perimeter which fronts a public way or open space having 20 feet minimum width = _____ (F)
- Total Building Perimeter = _____ (P)
- Ratio (F/P) = _____ (F/P)
- W = Minimum width of public way = _____ (W)
- Percent of frontage increase $I_f = 100 [F/P - 0.25] \times W/30 = \text{_____} (\%)$

² The sprinkler increase per Section 506.3 is as follows:

- Multi-story building $I_s = 200$ percent
- Single story building $I_s = 300$ percent

³ Unlimited area applicable under conditions of Sections Group B, F, M, S, A-4 (507.1, 507.2, 507.3, 507.5); Group A motion picture (507.8); Malls (402.6); and H-2 aircraft paint hangers (507.6).

⁴ Maximum Building Area = total number of stories in the building x E but not greater than 3 x E.

⁵ The maximum area of parking garages must comply with 406.3.5. The maximum area of air traffic control towers must comply with 412.1.2.

ALLOWABLE HEIGHT

	ALLOWABLE (TABLE 503)	INCREASE FOR SPRINKLERS	SHOWN ON PLANS	CODE REFERENCE
Type of Construction	Type _____		Type _____	
Building Height in Feet	Feet _____	Feet = H + 20' = _____		
Building Height in Stories	Stories _____	Stories + 1 = _____	Stories	

FIRE PROTECTION REQUIREMENTS

Life Safety Plan Sheet #, if Provided _____

BUILDING ELEMENT	FIRE SEPARATION DISTANCE (FEET)	RATING		DETAIL # AND SHEET #	DESIGN # FOR RATED ASSEMBLY	DESIGN # FOR RATED PENETRATION	DESIGN # FOR RATED JOINTS
		REQ'D	PROVIDED (w/_____*) REDUCTION)				
Structural frame, including columns, girders, trusses							
Bearing walls							
Exterior							
North							
East							
West							
South							
Interior							
Nonbearing walls and partitions							
Exterior							
North							
East							
West							
South							
Interior							
Floor construction Including supporting beams and joists							
Roof construction Including supporting beams and joists							
Shafts - Exit							
Shafts - Other							
Corridor Separation							
Occupancy Separation							
Party/Fire Wall Separation							
Smoke Barrier Separation							
Tenant Separation							

* Indicate section number permitting reduction

LIFE SAFETY SYSTEM REQUIREMENTS

Emergency Lighting: No Yes
 Exit Signs: No Yes
 Fire Alarm: No Yes
 Smoke Detection Systems: No Yes
 Panic Hardware: No Yes

EXIT REQUIREMENTS

NUMBER AND ARRANGEMENT OF EXITS

FLOOR, ROOM OR SPACE DESIGNATION	MINIMUM ² NUMBER OF EXITS		TRAVEL DISTANCE		ARRANGEMENT MEANS OF EGRESS ^{1,3} (SECTION 1004.1)	
	REQUIRED	SHOWN ON PLANS	ALLOWABLE TRAVEL DISTANCE (TABLE 1004.2.4)	ACTUAL TRAVEL DISTANCE SHOWN ON PLANS	REQUIRED DISTANCE BETWEEN EXIT DOORS	ACTUAL DISTANCE SHOWN ON PLANS

- ¹ Corridor dead ends (Section 1004.3.2.3)
² Single exits (Table 1005.2.2)
³ Common Path of Travel (Section 1004.2.5)

EXIT WIDTH

USE GROUP OR SPACE DESCRIPTION	(a)	(b)	(c)		EXIT WIDTH (in) ^{2,3,4,5,6}			
	AREA ¹ sq. ft.	AREA ¹ PER OCCUPANT (TABLE 1003.2.2.2)	EGRESS WIDTH PER OCCUPANT (TABLE 1003.2.3)		REQUIRED WIDTH (SECTION 1003.2.3) (a÷b) x c		ACTUAL WIDTH SHOWN ON PLANS	
			STAIR	LEVEL	STAIR	LEVEL	STAIR	LEVEL

- ¹ See Table 1003.2.2.2 to determine whether net or gross area is applicable.
 See definition "Area, Gross" and "Area, Net" (Section 1002)
² Minimum stairway width (Section 1003.3.3); min. corridor width (Section 1004.3.2.2); min. door width (Section 1003.3.1)
³ Minimum width of exit passageway (Section 1005.3.3)
⁴ See Section 1003.2.2.7 for converging exits.
⁵ The loss of one means of egress shall not reduce the available capacity to less than 50 percent of the total required (Section 1003.2.3)
⁶ Assembly occupancies (Section 1008)

STRUCTURAL DESIGN

DESIGN LOADS:

Importance Factors: Wind (I_w) _____
 Snow (I_s) _____
 Seismic (I_E) _____

Live Loads: Roof _____ psf
 Mezzanine _____ psf
 Floor _____ psf

Snow Load: _____ psf

Wind Load: Basic Wind Speed _____ mph (ASCE-7-98)
 Exposure Category _____
 Wind Base Shears (for MWFRS) $V_x =$ _____ $V_y =$ _____

SEISMIC DESIGN CATEGORY A

Compliance with Section 1616.4 only? Yes No

SEISMIC DESIGN CATEGORY B, C, & D

Provide the following Seismic Design Parameters:

Seismic Use Group _____

Spectral Response Acceleration S_{MS} _____ %g S_{M1} _____ %g

Site Classification _____

Basic structural system (check one)
 Bearing Wall Dual w/Special Moment Frame
 Building Frame Dual w/Intermediate R/C or Special Steel
 Moment Frame Inverted Pendulum

Seismic base shear $V_x =$ _____ $V_y =$ _____

Analysis Procedure Simplified Equivalent Lateral Force Modal

Architectural, Mechanical, Components anchored? _____

LATERAL DESIGN CONTROL: Earthquake _____ Wind _____

SOIL BEARING CAPACITIES:

Field Test (provide copy of test report) _____ psf
 Presumptive Bearing capacity _____ psf
 Pile size, type, and capacity _____

PLUMBING FIXTURE REQUIREMENTS

OCCUPANCY	WATERCLOSETS		URINALS	LAVATORIES		SHOWER/S/ TUBS	DRINKING FOUNTAINS	
	MALE	FEMALE		MALE	FEMALE		REGULAR	ACCESSIBLE

ACCESSIBLE PARKING

LOT OR PARKING AREA	TOTAL # OF PARKING SPACES		# OF ACCESSIBLE SPACES PROVIDED		TOTAL # ACCESSIBLE PROVIDED
	REQUIRED	PROVIDED	REGULAR WITH 5' ACCESS AISLE	VAN SPACES WITH 8' ACCESS AISLE	
TOTAL					

SPECIAL APPROVALS

Special approval: (Local Jurisdiction, Department of Insurance, SBCCI, ICC, etc., describe below)

ENERGY SUMMARY

ENERGY REQUIREMENTS:

The following data shall be considered minimum and any special attribute required to meet the energy code shall also be provided. Each Designer shall furnish the required portions of the project information for the plan data sheet. If energy cost budget method, state the annual energy cost budget vs allowable annual energy cost budget.

THERMAL ENVELOPE

Method of Compliance:

Prescriptive Performance Energy Cost Budget

Roof/ceiling Assembly (each assembly)

Description of assembly
U-Value of total assembly
R-Value of insulation
Skylights in each assembly
 U-Value of skylight
 total square footage of skylights in each assembly

Exterior Walls (each assembly)

Description of assembly
U-Value of total assembly
R-Value of insulation
Openings (windows or doors with glazing)
 U-Value of assembly
 shading coefficient
 projection factor
 low e required, if applicable
Door R-Values

Walls adjacent to unconditioned space (each assembly)

Description of assembly
U-Value of total assembly
R-Value of insulation
Openings (windows or doors with glazing)
 U-Value of assembly
 Low e required, if applicable
Door R-Values

Walls below grade (each assembly)

Description of assembly
U-Value of total assembly
R-Value of insulation

Floors over unconditioned space (each assembly)

Description of assembly
U-Value of total assembly
R-Value of insulation

Floors slab on grade

Description of assembly
U-Value of total assembly
R-Value of insulation
Horizontal/vertical requirement
slab heated

ELECTRICAL SUMMARY

ELECTRICAL SYSTEM AND EQUIPMENT

Method of Compliance:

Prescriptive Performance Energy Cost Budget

Lighting schedule

lamp type required in fixture
number of lamps in fixture
ballast type used in the fixture
number of ballasts in fixture
total wattage per fixture
total interior wattage specified vs allowed
total exterior wattage specified vs allowed

Equipment schedules with motors (not used for mechanical systems)

motor horsepower
number of phases
minimum efficiency
motor type
of poles

MECHANICAL SUMMARY

MECHANICAL SYSTEMS, SERVICE SYSTEMS AND EQUIPMENT

Method of Compliance

Prescriptive Energy Cost Budget

Thermal Zone

winter dry bulb
summer dry bulb

Interior design conditions

winter dry bulb
summer dry bulb
relative humidity

Building heating load

Building cooling load

Mechanical Spacing Conditioning System

Unitary

- description of unit
- heating efficiency
- cooling efficiency
- heat output of unit
- cooling output of unit

Boiler

- total boiler output. If oversized, state reason.

Chiller

- total chiller capacity. If oversized, state reason.

List equipment efficiencies

Equipment schedules with motors (mechanical systems)

- motor horsepower
- number of phases
- minimum efficiency
- motor type
- # of poles
